

# TECHNICAL DATA SHEET

**40810P**

## Econo-Spray 3 Release Aerosol



### Product Description

Econo-Spray® 3 contains a highly effective non-silicone release in a non-chlorinated solvent carrier system. This product is highly paintable, and will permit ultra-sonic welding of molded parts. It affords excellent release of all thermoplastics.

### Applications

Mold Release

### Unit Package Description

16 ounce aerosol

### Generic Description

Paintable Mold Release

### Net Weight Fill

10 net ounces

### UPC Code

858799000080

### Units Per Case

12

### Case Weight (lbs)

12

### Appearance

Clear Oily Colorless Liquid

### Flash Point F

Not Determined

### Flash Point C

Not Determined

### Base Type

Propylene Glycol

### Evaporation Rate

Fast

### Working Temperature F

32 to 600 degrees

### Working Temperature C

0 to 315 degrees

### Propellant

Propane

### NFPA Aerosol Flammability Level

3

### DOT Proper Shipping Name

UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

### VOC % (Federal)

97

### VOC g/L (Federal)

613

### VOC lbs./Gal (Federal)

5.12

### Removal

Remove with organic or hydrocarbon solvents

### Food Safety Citation (CFR)

21CFR 178.3570