


# KG5065



## Capacitive sensor

KG-3120NFAKGP2T/US



- 1 LED ring
- 2 Programming buttons



### Product characteristics

Electrical design	PNP/NPN; (Automatic load detection PNP/NPN; when using a resistive load < 20 kΩ)
Output function	normally open / closed; (selectable)
Sensing range [mm]	12
Communication interface	IO-Link
Housing	Threaded type
Dimensions [mm]	M18 x 1 / L = 87

### Electrical data

Operating voltage [V]	10...36 DC
Current consumption [mA]	< 20
Protection class	II
Reverse polarity protection	yes

### Outputs

Electrical design	PNP/NPN; (Automatic load detection PNP/NPN; when using a resistive load < 20 kΩ)
Output function	normally open / closed; (selectable)
Max. voltage drop switching output DC [V]	2.5
Permanent current rating of switching output DC [mA]	200
Switching frequency DC [Hz]	10
Short-circuit proof	yes
Overload protection	yes

### Monitoring range

Sensing range [mm]	12
--------------------	----

### Accuracy / deviations

Hysteresis [% of Sr]	1...15
Switch-point drift [% of Sr]	-20...20

# KG5065



## Capacitive sensor

KG-3120NFAKGP2T/US

Interfaces		
Communication interface	IO-Link	
Transmission type	COM1 (4,8 kBaud)	
IO-Link revision	1.1	
SDCI standard	IEC 61131-9 CDV	
Profiles	Smart Sensor	
SIO mode	yes	
Min. process cycle time [ms]	101	
Supported DeviceIDs	Type of operation	DeviceID
	default	387

Operating conditions	
Ambient temperature [°C]	-25...80
Note on ambient temperature	temperature of the sensing face: -25...110 °C
Protection	IP 65; IP 67

Tests / approvals		
EMC	EN 61000-4-2 ESD	8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-6 HF conducted	3 V
	EN 55011	class B
Vibration resistance	EN 60068-2-6 Fc	(10...55 Hz) / 1 mm amplitude, vibration duration 5 min., 30 min. per axis with resonance or 55 Hz
Shock resistance	EN 60068-2-27 Ea	30 g 6 shocks / 11 ms half-sine (x, y, z)
MTTF [years]	566	

Mechanical data	
Weight [g]	31.5
Housing	Threaded type
Mounting	non-flush mountable
Dimensions [mm]	M18 x 1 / L = 87
Thread designation	M18 x 1
Material	housing: PBT; Pushbuttons: TPE-U; LED window: PC

Displays / operating elements		
Display	Switching status	1 x LED, yellow
Teach function	yes	
Electronic lock	yes	

Accessories	
Items supplied	lock nuts: 2

Remarks	
Pack quantity	1 pcs.



Electrical connection - plug	
Connector: 1 x M12	

# KG5065



## Capacitive sensor

KG-3120NFAKGP2T/US



- 4:                   OUT / IO-Link  
Automatic load detection PNP/NPN  
when using a resistive load < 20 k $\Omega$